

Cirrus 80



Cirrus 80			
Nominal Power output	at 10°C	300 / 600 W	450 / 800 W
Recommended fuse	at 115 V / 230 V	5	6
Time delay	Amps		
Fan volumetric flow, approximate	(m ³ /hr)	35	35
Fan lifetime	at 40°C L10, hours	43,500	43,500
Fan operating temperature	°C	- 40 to +50	- 40 to +50
Nominal Input voltage		115 V / 230 VAC	115 V / 230 VAC
Dimensions (mm)	cross section	82 x 110	82 x 110
	length	150	150
Ingress Protection		IP 20	IP 20
Weight	(kg)	0.785	0.785
Finger guards	inlet and outlet	Y	Y

Ordering Example:

Type	Power	Heater Voltage	DIN clip	Filter
			1 / 0	1 / 0
C80	600 W	230 V	1	1

Order Code Example: C80 – 600 W – 230 V – 1 – 1

Features:

- High power to size ratio
- Lightweight
- Easy to fit
- Screw terminals for easy wiring
- Dual power feature
- Independent fan circuit to aid climate cooling

Options:

- Filter Assembly*
- Fixings - 35mm DIN Rail clip (EN50022)



* Typical power reduction of 10% when 30 PPI filter fixed. Data is given for illustration purposes only and does not release the customer from independent application tests.